



## Technical data

V-BIO	Length [mm]	Width [mm]	Height [mm]	Capacity [m <sup>2</sup> ] approx.	Max. payload [kg]	Dosing augers	Recomm. gear motor for EnergySave auger
8-1S	3500	2150	2420	8	4.000	1	1 x 15 kW
10-1S	3800	2150	2830	10	5.000	1	1 x 15 kW
12-1S	3800	2150	3130	12	6.000	1	1 x 22 kW
14-1S	4200	2450	2700	14	7.000	1	1 x 22 kW
16-1S	4200	2450	3000	16	8.000	1	1 x 22 kW
18-1S	4200	2450	3300	18	9.000	1	1 x 30 kW
25-2S	6600	2450	2700	25	12.500	2	2 x 22 kW
30-2S	6600	2450	3000	30	16.000	2	2 x 22 kW
35-2S	6600	2450	3300	35	17.500	2	2 x 22 kW
40-2S	6600	3000	3600	40	20.000	2	3 x 37 kW
38-3S	9000	2450	2700	38	19.000	3	3 x 22 kW
45-3S	9000	2450	3000	45	22.500	3	3 x 22 kW
50-3S	9000	2450	3300	50	25.000	3	3 x 22 kW
60-3S	9000	3000	3500	60	30.000	3	3 x 30 kW
80-3S	9000	3000	4300	80	40.000	3	3 x 37 kW
V-BIO Combi	Width [mm]	Width [mm]	Height [mm]	Capacity [m <sup>2</sup> ] approx.	Max. payload [kg]	Dosing augers	Recomm. gear motor for EnergySave augers + hydraulics
60-1S 1D	11000	2500	3500	55	30.000	1	1 x 22 kW + 1 x 3 kW
80-1S 2D	17600	2500	3100	80	40.000	1	1 x 22 kW + 2 x 3 kW
90-2S 1D	9280	6470	3800	90	45.000	2	2 x 30 kW + 1 x 3 kW
100-1S 2D	17600	2500	3500	100	50.000	1	1 x 22 kW + 2 x 3 kW
150-2S 2D	17850	6470	3800	150	75.000	2	2 x 30 kW + 2 x 3 kW